

WEDOLiT CS 8208

Water-miscible, fully synthetic coolant



WEDOLiT CS 8208 is suitable for ultrasonic testing systems. The product is also suitable for the manufacturing of welded steel tubes. It fulfils the requirements regarding lubrication and cleanliness of the tubes and rollers as well as the corrosion protection of the tubes and the system (in a concentration of 5 - 10%). Not suitable for the manufacturing of workpieces made of zinc, aluminum and their alloys.



Physical Properties Typical Data

Concentrate

| Color | Mineral oil content | Viscosity at 68°F: ASTM D 7042 | Density at 68°F: ASTM D 7042 | Copper corrosion: DIN 51759-1 |
|--------|---------------------|-----------------------------------|---------------------------------|----------------------------------|
| Yellow | Free | 9.0 cSt | 1.10 | Not determined* |

5% Solution

| Color | pH-value (tap water) | Corrosion protection DIN 51360-2 | Refractometer factor (brix) | Conductivity (Deionized water) |
|-------------|-------------------------|-------------------------------------|--------------------------------|-----------------------------------|
| Transparent | 9.4 | 5 % grade 0 | 1.9 | 2270 µS/cm |

| Mineral oil | EP-additives | Chlorine | Boron | Amines | FAD |
|-------------|--------------|----------|-------|--------|-----|
| - | - | - | + | + | + |

*Discolorations of non-ferrous metals should be examined in preliminary tests

Application Guidelines

The preparation of the solution is carried out by slowly adding the concentrate into water (drinking water quality) under thorough stirring. A more homogenous product is achieved by the use of automatic mixing systems.

Storage must be frost-free between 41 - 104°F.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/diw/?plr=CS-8208*en-ap*ap

WEDOLiT CS 8208

©2020-2025 Master Fluid Solutions™ | 2025-12-08

Choose WEDOLiT CS 8208:

- Offers high cooling- and flushing properties with a very good wetting behavior
- Contributes to a high tool life
- Very good application stability
- Almost free of foam
- Offers a good skin compatibility
- Due to its thermal stability, the product can be used in almost the whole process chain of welded tubes (forming, welding, calibration, sawing)

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

501 West Boundary Street
Perrysburg, OH 43551-1200
United States
+1 419-874-7902

info@masterfluids.com

masterfluids.com/ap/en-ap/

