


# WEDOLiT FS 3710

## Evaporating Drawing-oil

WEDOLiT FS 3710 is a non-water soluble, synthetic cooling lubricant of low viscosity. It is applicable for drawing- and punching-operations of aluminium. Can be applied undiluted by spraying, flooding, brushing or rolling.



### Physical Properties Typical Data

:		
:	0.00	
:	0.0	
:	0	
:		

### Application Guidelines

Storage must be frost-free between 5 - 40°C.

The minimum durability is 24 months in an original sealed package.

### Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

[https://2trim.us/diw/?plr=FS-3710\\*en-ap\\*ap](https://2trim.us/diw/?plr=FS-3710*en-ap*ap)

WEDOLiT FS 3710

©2018-2024 Master Fluid Solutions™ | 2024-11-21



### Choose WEDOLiT FS 3710:

- Good wetting of the metal surface
- Nearly odourless
- Despite the good lubrication properties, the product is characterised by a quick evaporation and high flash point
- The working area should be sufficiently ventilated, due to the amount of volatile hydrocarbons

### Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.