

TRIM™ TC 230

Bio-stabilizer

TRIM TC 230 is an active bio-stabilizer that kills all types of bacteria, fungi, and microorganisms. TRIM TC 230 prolongs coolant life, is environmentally friendly, and can be broadly applied to most coolants.

Additives



The troubleshooters:

As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.

Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.



Choose TC 230:

TC 230 especially for:
Applications — stabilizer

Health and Safety

Request SDS



TRIM™ TC 230

Bio-stabilizer



Application Guidelines

- TRIM TC230 is added at a rate of 0.1% to working solutions. This product should not be added at a rate in excess of 0.2%, except as recommended by technical engineers from Master Fluid Solutions.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/ap/en-ap/distributors/index.php>, your District Sales Manager, or email us at apac-info@masterfluids.com.

Physical Properties Typical Data

Color (Concentrate)	Clear light yellow
Odor (Concentrate)	Slight characteristic
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 111°C
pH (Concentrate as Range)	10.3 - 11.3

Ordering Information

20-liter pail

204-liter drum

1000-liter tote

TRIM™ TC 230 | ©2024-2026 Master Fluid Solutions™ | 2026-02-04

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=ap_en-ap_TC230



B-41, Chakan MIDC Phase - 2, Village
Bhambuli,
Post Vasuli, Tal. Khed, Pune -410 501.
Maharashtra,
India

india-info@masterfluids.com

[masterfluids.com/ap/en-ap/](https://www.masterfluids.com/ap/en-ap/)

