

WEDOLIT[®] AN 6999

**High-Protection-Fluid 170°C flash point
(aromatic content ≤ 2%)**



WEDOLIT AN 6999 is a modern formulated corrosion inhibitor for steel and other metals. It offers long-term corrosion protection (indoor storage and potentially outdoor storage) and can be applied by brushes or by means of rollers.



Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Brown	Visual
Density at 15°C:	0.91 g/cm ³	ASTM D 7042
Viscosity at 20°C:	Not measurable	ASTM D 7042
Flash point:	> 170 °C	DIN EN ISO 2719
Film weight:	Depending on the application	Dipping procedure
Film type:	Greasy	Haptical
Dewatering effect:	None	Internal test method
Water separation:	None	Internal test method
Humidity test:	1500 cycles	DIN EN ISO 6270-2 AHT
Salt spray performance:	250 h	DIN EN ISO 9227 NSS

Application Guidelines

Storage must be frost-free between 10 - 30°C.

The minimum durability is 12 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=AN-6999*en*eu

WEDOLIT[®] AN 6999

©2022-2024 Master Fluid Solutions™ | 2024-11-21

Choose WEDOLIT AN 6999:

- Ideal for overseas transport
- Suitable for VCI-foils
- Good protection for outdoor storage
- Stable against acidic and alkaline contamination
- Good material compatibility
- Easily removable with organic solvents (cold cleaners) or water-miscible alkaline industrial cleaners
- Ideal for covered storage
- Offers protection against atmospheric contamination, e.g. dissolved gases that cannot penetrate the protecting film (water vapour permeability)

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

