


WEDOLiT CN 2370-7

High Performance Grinding Oil

WEDOLiT CN 2370-7 is a low viscous, high performance grinding oil based on the latest gas to liquid (GTL) technology. GTL-base-oils are free of aromatics, chlorine, zinc, nitrogen and heavy metals, to provide the best occupational safety for the worker. The product is suitable for the machining of HSS and carbides (especially with a high cobalt content). The product is also suitable for general cutting operations as well as for gear hobbing.



Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Yellowish, clear	Visual
Density at 20°C:	0.80 g/cm ³	ASTM D 7042
Viscosity at 40°C:	7.0 mm ² /s	ASTM D 7042
Flash point:	> 160 °C	DIN EN ISO 2719
Copper corrosion:	1a	DIN 51759-1

Application Guidelines

Storage must be frost-free between 5 - 40°C.


The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=CN-2370-7*en*eu

WEDOLiT CN 2370-7

©2016-2024 Master Fluid Solutions™ | 2024-07-03



Choose WEDOLiT CN 2370-7:

- High performance product, which leads to an excellent surface finish and dimensional accuracy
- Highly reduced oil mist formation, almost no loss of evaporation
- Reduces friction and wear and thus contributes to a long tool life
- Offers high cooling properties with a very good wetting behaviour
- Very good flushing behaviour with an optimal transport of chips and swarf
- Easily removable with organic solvents or alkaline industrial cleaners

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14
Düsseldorf, 40597
Germany
+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

