

# WEDOLIT® KS 3000

## Multi-purpose oil

WEDOLIT KS 3000 is a universally applicable corrosion protection/ rust remover which is also effective in case of moisture-related ignition problems of electrical systems. The product protects chrome parts, tools and machines from atmospheric influences, loosens rusted screws, joints, hinges, switches, cleans tools and parts and protects them from corrosion.



### Physical Properties Typical Data

Parameter	Typical results	Tested according to
Appearance:	Medium brown, clear	Visual
Density at 20°C:	0.80 g/cm <sup>3</sup>	ASTM D 7042
Film weight:	1.8 g/m <sup>2</sup>	Dipping procedure
Film type:	Oily	Haptical
Dewatering effect:	≤ 60 s	Internal test method
Humidity test:	70 cycles	DIN EN ISO 6270-2 AHT
Salt spray performance:	8 h	DIN EN ISO 9227 NSS
VKA-value:	> 3800 N (typ. 3900 N)	DIN 51350 T2

### Application Guidelines

Spray from a distance of 10 - 20 cm and allow to absorb for approx. 5 minutes. An exposure time of approx. 10 minutes is recommended to loosen firmly rusted parts.

Storage must be frost-free between 5 - 40°C.

The minimum durability is 12 months in an original sealed package.

### Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL: [https://2trim.us/diw/?plr=KS-3000\\*en\\*eu](https://2trim.us/diw/?plr=KS-3000*en*eu)

WEDOLIT® KS 3000

©2016-2024 Master Fluid Solutions™ | 2024-07-22



### Choose WEDOLIT KS 3000:

- Very good creep behaviour (penetrates even very small cavities)
- Loosens rusted joints
- Stops squeaking
- Provides temporary protections against corrosion
- Very good lubrication properties even at low temperatures
- To remove heavy staining or corrosion, it might be necessary to repeat the application
- Water displacing with a very good wetting behaviour
- Suitable for spot lubrication (e.g. for drilling operations)

### Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

Hasselsstraße 6-14  
Düsseldorf, 40597  
Germany  
+49 211 41 72 82 00

[info-eu@masterfluids.com](mailto:info-eu@masterfluids.com)

[masterfluids.com/eu/en/](https://www.masterfluids.com/eu/en/)

