

TRIM™ MicroSol™ 690XT

High-lubricity, Low-foam Premium Semisynthetic

TRIM MicroSol 690XT is a high-lubricity, semisynthetic, microemulsion coolant. The formula delivers extended sump life and better foam control versus previous generation semisynthetics. It provides excellent cooling and mechanical lubricity, along with the machine friendly characteristics you expect from a premium TRIM coolant. It does very well in mixed metal situations and is compatible with a very wide range of materials including titanium, high nickel alloys, steels, copper and aluminium alloys.

Asian Automotive Manufacturer Enhances Operations with MicroSol™ 690XT



As a large automotive parts and components manufacturer, the customer specialises in die-cast aluminium engine heads and powdered metal valve seats. Their high-volume operation produces superior precision parts with top-quality finishes. As the company looks to the future, they are interested in implementing environmentally friendly production methods.

Aerospace Approvals

Company	Specification
Fokker	No specification available
GE Aerospace	SDS# EVEN-12659
Lockheed Martin/Sikorsky	864-009
Northrop Grumman	No specification available
Raytheon Technologies/Collins Aerospace/Pratt & Whitney	PMC 9293
Rolls-Royce	No specification available
Safran Group	PCS-4001/4002, PR6300



Choose MicroSol 690XT:

- Dramatically extends useful life without the need for tank-side biocides or fungicides
- Boron and halogen free
- Low foaming for today's demanding high-pressure, high-volume applications
- Compatible with a very wide range of materials including titanium, high nickel alloys, steels, copper and aluminium alloys
- Excellent alternative to chlorinated soluble oils on high-silica aluminium alloys
- Contains no nitrates, triazines, phenols, chlorinated or sulfured EP additives
- Provides superior corrosion inhibition on all ferrous and nonferrous metals
- Keeps machines very clean while leaving a soft fluid film for ease of cleaning and reduced maintenance
- Uses standard metalworking recycling and disposal techniques

MicroSol 690XT especially for:

Applications — band sawing, cylindrical form grinding, drilling, grinding, high-pressure, high-volume, internal grinding, plain grinding, reaming, roll threading, surface grinding, surface milling, tapping, thread forming, through-feed centreless grinding and turning

Metals — 6000 series aluminium, aerospace aluminium alloys, aluminium alloys, brass, bronze, cast aluminium, cast iron, composites, copper, copper alloys, exotic alloys, glass, heat-treated steel, high-carbon steel, high-nickel alloys, high-silica aluminium alloys, nonferrous metals, plastics, stainless steels, steels, titanium and wrought aluminium

Industries — aerospace, automotive, bearing, compressor, diecast, energy, green, job shop, machine tool and medical

MicroSol 690XT is free of — boron, chlorinated EP additives, formaldehyde releasers, halogens, nitrates, phenols and sulphurised EP additives

TRIM™ MicroSol™ 690XT

High-lubricity, Low-foam Premium Semisynthetic



Application Guidelines

- MicroSol 690XT performs well where traditional soluble oils may not cool sufficiently.
- In mixed-metal situations, concentration control is critical to fight galvanic corrosion (7.5% plus).
- Running at or above 7.5% offers the best sump life and corrosion inhibition on cast iron chips.
- Please use safe handling precautions including proper ventilation when machining reactive materials such as magnesium.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.masterfluids.com/eu/en/distributors/index.php>, your District Sales Manager, or call our Tech Line at +49 211 41 72 8 -900.


Physical Properties Typical Data

Colour (Concentrate)	Light yellow
Colour (Working Solution)	White microemulsion
Odour (Concentrate)	Mild amine
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 160°C
pH (Concentrate as Range)	9.6 - 10.6
pH (Typical Operating as Range)	9.4 - 10.4
Coolant Refractometer Factor	1.2
Titration Factor (CGF-1 Titration Kit)	0.64


Recommended Metalworking Concentrations

Light Duty	5.0% - 6.5%
Moderate Duty	6.5% - 8.5%
Heavy Duty	8.5% - 10.0%
Design Concentration Range	5.0% - 10.0%

Concentration by % Brix



Concentration by Titration



Health and Safety

Request SDS



TRIM™ MicroSol™ 690XT

High-lubricity, Low-foam Premium Semisynthetic



Mixing Instructions

- Recommended usage concentration in water: 5.0% - 10.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.
- Use premixed coolant as makeup to improve coolant performance and reduce coolant purchases. The makeup you select should balance the water evaporation rate with the coolant carryout rate. Use our Coolant Makeup Calculator to find the best ratio for your machine: apps.masterfluids.com/makeup/.
- Use mineral-free water to improve sump life and corrosion inhibition while reducing carryoff and concentrate usage.

Ordering Information

20-litre pail

204-litre drum

1000-litre IBC

TRIM™ MicroSol™ 690XT | ©2014-2026 Master Fluid Solutions™ | 2026-01-28

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM™ and MicroSol™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=eu_en_MS690XT



Hasselstraße 6-14

Düsseldorf, 40597

Germany

+49 211 41 72 82 00

info-eu@masterfluids.com

masterfluids.com/eu/en/

