

# TRIM™ SC440SW

## Low foam Semisynthetic

TRIM SC440SW is a very low foam, semisynthetic coolant specifically formulated for machining and grinding of cast iron and steel in soft water. This unique formulation ensures low levels of foam not generally seen with other semisynthetic products. SC440SW's clean running formulation also prevents the loading of grinding wheels, ensuring good surface finishes and minimal burning.

### Semisynthetics



#### Cutting edge solutions:

TRIM® semisynthetics offer the cooling and lubricity of a synthetic without the higher oil content of a soluble oil. Designed to operate at higher SFPM, semisynthetics perform well on many operations including face milling, cut-off turning, grinding, tapping and drilling — depending on the specific product.

Semisynthetics are compatible with alloy steels, tool steels, cast irons, copper alloys, as well as plastics and composites. With less carryoff, semisynthetics use less material — it all adds up to lower costs.



### Choose SC440SW:

- No aggressive biocides
- Low foaming even in soft water
- Excellent rust protection to prevent clinkering of cast iron chips
- Keeps the machine and work environment clean even when machining or grinding grey iron
- Fine micro-emulsion reduces carry-off for low total operating cost
- Fast wetting to get the fluid to the point of cut and keep grinding wheels clean
- Easily recycled or disposed of without special handling or equipment

### SC440SW especially for:

**Applications** — centreless grinding, drilling, grinding, high-pressure, machining, milling, plain grinding, surface grinding and turning

**Metals** — cast iron and steel alloys

**Industries** — automotive, bearing, compressor and general industry

**SC440SW is free of** — boron, chlorine, formaldehyde releasers, nitrates, secondary amines and sulphurised EP additives

# TRIM™ SC440SW

## Low foam Semisynthetic

### Application Guidelines

- Runs effectively for long periods without the need for costly additives.
- Run at lower concentrations for higher speed operations (where heat removal is the key issue).
- Higher concentrations are recommended on soft, gummy materials and for lower speed operations where friction reduction and control of built-up edge are critical.
- Concentrations above 7% provide the best sump life.
- For additional product application information, including performance optimisation, please contact your Master Fluid Solutions' Authorised Distributor at <https://www.masterfluids.com/eu/en/distributors/index.php>, your District Sales Manager, or call our Tech Line at +49 211 41 72 8 -900.

### Physical Properties Typical Data


Colour (Concentrate)	Light yellow
Colour (Working Solution)	Translucent
Odour (Concentrate)	Bland
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D93-08)	> 150°C
pH (Concentrate as Range)	9.4 - 9.7
pH (Typical Operating as Range)	9.6 - 9.9
Coolant Refractometer Factor	2.7
Digital Titration Factor	0.0230

### Recommended Metalworking Concentrations

Light Duty	5.0% - 7.0%
Moderate Duty	7.0% - 9.0%
Heavy Duty	9.0% - 10.0%
Design Concentration Range	5.0% - 10.0%



### Concentration by % Brix



### Health and Safety

Request SDS



# TRIM™ SC440SW

## Low foam Semisynthetic

### Mixing Instructions

- Recommended usage concentration in water: 5.0% - 10.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.
- Use premixed coolant as makeup to improve coolant performance and reduce coolant purchases. The makeup you select should balance the water evaporation rate with the coolant carryout rate. Use our Coolant Makeup Calculator to find the best ratio for your machine: [apps.masterfluids.com/makeup/](https://apps.masterfluids.com/makeup/).
- Use mineral-free water to improve sump life and corrosion inhibition while reducing carryoff and concentrate usage.

### Ordering Information

20-litre pail

204-litre drum

1000-litre IBC


TRIM™ SC440SW | ©2019-2026 Master Fluid Solutions™ | 2026-01-28



### Additional Information

- Use Master STAGES™ Whamex XT™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex XT™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

[https://2trim.us/di/?i=eu\\_en\\_SC440SW](https://2trim.us/di/?i=eu_en_SC440SW)



Hasselstraße 6-14

Düsseldorf, 40597

Germany

+49 211 41 72 82 00

[info-eu@masterfluids.com](mailto:info-eu@masterfluids.com)

[masterfluids.com/eu/en/](http://masterfluids.com/eu/en/)