

TRIM[®] TC 108

Metalworking Fluid Defoamer

TRIM TC 108 is a highly effective tank side additive used to control foam in metalworking fluid systems.

Additives



The troubleshooters:

As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM™ tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.

Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.



Choose TC 108:

- Paintable
- Plateable

TC 108 especially for:

Applications — antifoam

Health and Safety

Request SDS



TRIM[®] TC 108

Metalworking Fluid Defoamer



Application Guidelines

- Start by adding 1 to 3 ounces of TC 108 per 100 gallons of solution (8 to 24 ml per 100 liters) to lower foam (100-200 ppm in tank side usage). You may find that using less than this will be effective in your system.
- Shake or stir well before adding. For best results, premix TC 108 in a separate container with working solution until it is water-thin. This mixture should be added just up-stream from the foam.
- The maximum amount of TC 108 in the system should not exceed 16 ounces per one hundred gallons (128 ml per 100 liters) of metalworking fluid. Using too much TC 108 can cause foam and/or form a residue on the machine, parts, or tools.
- Spraying premixed TC 108 directly onto the foam will also knock it down quickly.
- Do not freeze or store above 115°F (46°C).
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/in/en-in/distributors/index.php>, your District Sales Manager, or email us at india-info@masterfluids.com.

Physical Properties Typical Data

| | |
|---|-----------------------|
| Color (Concentrate) | Opaque white |
| Odor (Concentrate) | Slight characteristic |
| Form (Concentrate) | Liquid |
| Flash Point (Concentrate) (ASTM D92-90) | > 107°C |

Ordering Information


20-litre pail
204-liter drum
1000-litre IBC

TRIM[®] TC 108 | ©2024 Master Fluid Solutions[®] | 2024-11-23

Additional Information

- Use Master STAGES[™] Whamex[™] for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM[™] is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES[™] and Whamex[™] are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=in_en-in_TC108



B-41, Chakan MIDC Phase - 2, Village
Bhambuli,
Post Vasuli, Tal. Khed, Pune -410 501.
Maharashtra,
India
+91 2135 675961

india-info@masterfluids.com

[masterfluids.com/in/en-in/](https://www.masterfluids.com/in/en-in/)