TRIM® OE315 NS

Vegetable Ester Based Cutting Oil

TRIM OE315 NS is a heavy-duty straight cutting oil formulated using renewable vegetable esters. For use in very tough machining operations of hardened steel alloys, tool steels, and stainless steels. TRIM OE315 NS is especially effective in deep hole drilling applications due to its reasonably low viscosity, lubricity, and EP performance.

Straight Oils



Straight to the point-of-cut:

TRIM straight oils, used "straight up" without dilution of water, provide maximum lubricity. TRIM neat oils have super lubrication and extreme pressure ability, which effectively protects the tool, prolongs its service life, and can obtain extremely high workpiece precision and surface finish.

Depending on the specific product, some TRIM straight oils are a high-end blend of various base oils; while others contain extreme-pressure additives to control built-up edge and prolong tool life.

Get straight to the cut with TRIM straight oils.

Choose OE315 NS:

- Excellent extreme-pressure additive package for efficient metal removal
- Extremely high lubricity ensures fantastic tool life
- Low viscosity ensures excellent chip removal in deep-hole drilling
- Ester based formulation ensures very low misting potential
- Very high flash point
- Good oxidation stability
- Compatible with copper containing alloys
- Light color and low odor for good operator acceptance

OE315 NS especially for:

Applications — deep hole drilling, drilling, gear cutting, gun drilling, machining, milling, reaming, tapping, and turning

Materials — aluminum, Inconel®, nickel alloys, stainless steels, steel alloys, titanium, and yellow metals

Industries — aerospace, automotive, general industry, and medical

OE315 NS is free of — chlorine and zinc

Health and Safety

Request SDS

Master Fluid SOLUTIONS®

TRIM® OE315 NS

Vegetable Ester Based Cutting Oil

Application Guidelines

- TRIM OE315 NS is designed to be used straight.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at https://www.masterfluids.com/na/en-us/distributors/index.php, your District Sales Manager, or call our Tech Line at 1-800-537-3365.

Physical Properties Typical Data

Color	Straw yellow
Odor	Mild
Form	Liquid
Flash Point	> 446°F
Viscosity	15.00 cSt @104°F (40°C)
V.O.C. Content (ASTM E1868-10)	2 g/l



1-gallon jug
SKU: OE315NS-1G
UPC-12: 641238077541



5-gallon pail
SKU: OE315NS-5G
UPC-12: 641238077527



54-gallon drum
SKU: OE315NS-54G
UPC-12: 641238076667



270-gallon tote
SKU: OE315NS-270G
UPC-12: 641238077565

Additional Information

- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM® is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=na_en-us_OE315NS

501 West Boundary Street
Perrysburg, OH 43551-1200
United States
+1 419-874-7902

info@masterfluids.com

masterfluids.com/na/en-us/