

# TRIM<sup>®</sup> TC 184B

## *Nonsilicone Antifoam*

TRIM TC 184B is a nonsilicone antifoam or defoamer. It is used as a tank-side add to control foam in water-miscible coolants, washing compounds, floor soaps, etc.

### **Additives**



#### **The troubleshooters:**

*As cutting and grinding fluids can start to break down over time, tank-side additives can solve a number of problems. There are TRIM tank-side additives compatible with most coolants to extend tap and tool life, improve mechanical lubricity, control built-up edge, prevent stained parts, control foam, stabilize the emulsion, and replenish dye.*

*Whatever your problems and concerns, ask your TRIM specialist if a tank-side additive could be the answer.*



#### **Choose TC 184B:**

- Antifoam
- Nonsilicone

#### **TC 184B especially for:**

**Applications** — antifoam

#### **Health and Safety**

Request SDS



# TRIM<sup>®</sup> TC 184B

## Nonsilicone Antifoam






### Application Guidelines

- The maximum add rate is one gallon per 1000 gallons of sump volume. You may find that using less than this will be effective in your system.
- For best results, pre-mix TC 184B with working solution until it is water-thin. This mixture should then be added just up-stream from the foam.
- Spraying pre-mixed TC 184B directly onto the foam will knock it down quickly.
- Using too much TC 184B can cause increased foam and/or form a residue on the machine parts or tools.
- Shake or stir well before adding. If you make a dilution with working solution, shake or stir that mixture also before adding.
- Do not freeze or store above 115°F.
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/na/en-us/distributors/index.php>, your District Sales Manager, or call our Tech Line at 1-800-537-3365.

### Physical Properties Typical Data

Color (Concentrate)	Opaque, white
Odor (Concentrate)	Slight
Form (Concentrate)	Liquid
Flash Point (Concentrate) (ASTM D92-90)	> 385°F



### Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM<sup>®</sup> is a registered trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

[https://2trim.us/di/?i=na\\_en-us\\_TC184B](https://2trim.us/di/?i=na_en-us_TC184B)



501 West Boundary Street  
Perrysburg, OH 43551-1200  
United States  
+1 419-874-7902

[info@masterfluids.com](mailto:info@masterfluids.com)

[masterfluids.com/na/en-us/](https://www.masterfluids.com/na/en-us/)