


WEDOLiT FN 8850-90

Drawing small diameter tubes, diesel injection



WEDOLiT FN 8850-90 is a medium viscous, water-insoluble lubricant for tube drawing and other cold forming operations of steel. Due to the fact that the product also offers corrosion protection, no additional treatment is necessary (for short term storage). The undiluted product is usually applied by spraying, brushes, or by means of rollers.



Physical Properties Typical Data

:		
:	0.00	
:	0.0	
:	0 °C	
:		

Application Guidelines

Storage must be frost-free between 41 - 104°F, (5 - 40°C).
The minimum durability is 24 months in an original sealed package.

Additional Information

The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:
https://2trim.us/diw/?plr=FN-8850-90*en-th*th

WEDOLiT FN 8850-90
©2020-2024 Master Fluid Solutions™ | 2024-07-22

Choose WEDOLiT FN 8850-90:

- Stable load carrying capacity and a homogenous sliding behavior
- Reduces friction and wear and thus contributes to a high tool life
- Outstanding wetting ability and film formation without adhesion
- Stable cold start behavior, prevents stick-slip and chatter
- Leads to clean surfaces and contributes to achieving dimensional accuracy
- Easily removable with organic solvents or alkaline industrial cleaners

Health and Safety

For further information, see the most recent SDS which is available directly from Master Fluid Solutions.

333/8 Moo 9, Bangpla, Bangplee
Samutprakarn, 10540
Thailand
+662 136 6319

thailand-info@masterfluids.com

[masterfluids.com/th/en-th/](https://www.masterfluids.com/th/en-th/)

