

TRIM™ DRIVE G81 NXT

Premium Cutting Fluid for HDD Manufacturing



TRIM DRIVE G81 NXT is a specialized, chlorine-free, moderate to heavy duty metal cutting fluid formulated to meet the high-precision machining and stringent chemical restrictions of the Hard Disk Drive (HDD) industry. TRIM DRIVE G81 NXT has very good wetting and lubricity giving excellent surface finishes. Its ease of washability makes TRIM DRIVE G81 NXT an excellent choice for HDD components manufacturers. TRIM DRIVE G81 NXT will run in high-pressure situations with little to no foam.

DRIVE



For ultimate performance:

DRIVE coolants deliver high-performance lubricity and ultimately lower costs. Achieve precision parts, exceptional tool life, extended sump life, assured regulatory compliance, and greater profitability with a product just right for your production. Designed to meet the rigorous demands of the HDD industry and high production, precision parts manufacturing industries, there is a TRIM Drive to answer your concerns, ramp up your production, and boost your bottom line.

Choose DRIVE G81 NXT:

- In addition to aluminum alloy, TRIM DRIVE G81 NXT is also suitable for a wide range of materials including steels, titanium, and stainless steels
- Low foam even in high-pressure operations without the use of silicone antifoam
- Good hydrodynamic lubrication to perform reaming and threading applications
- Excellent anti-weld properties without the use of either chlorinated or sulfurized EP additives
- Does not contain mineral oil for near zero hydrocarbon contamination level
- Keeps machines very clean while leaving a soft film that protects machine surface, for ease of cleaning and reduced machine maintenance costs
- Does not require special disposal and is easily recycled
- Designed to be used with deionize water without having any foam issues
- Non-staining on aluminum alloys commonly used to produce HDD components
- Parts machined with TRIM DRIVE G81 NXT can be washed easily and completely in aqueous washing systems

DRIVE G81 NXT especially for:

Applications — machining, milling, reaming, and thread forming

Metals — aluminum alloys, stainless steels, steels, and titanium

Industries — hard disk drives

DRIVE G81 NXT is free of — chlorinated EP additives, chlorine, mineral oils, and sulfurized EP additives

TRIM™ DRIVE G81 NXT

Premium Cutting Fluid for HDD Manufacturing



Application Guidelines

- Normally used at a concentration of 8.0% - 10.0% for moderate machining; for heavy-duty machining, use concentration between 10.0% - 12.0%.
- Higher concentrations of working solutions increases both hydrodynamic and EP lubrication; however, prolonged contact with concentrations more than 15.0% may result in skin irritation.
- Not recommended for use on cast iron, magnesium, or zirconium without special precautions. However, aluminum or zinc alloy with magnesium content is generally acceptable.
- Check with Master Fluid Solutions for the proper cleaner product which should be used before filling machine tanks with TRIM DRIVE G81 NXT
- For additional product application information, including performance optimization, please contact your Master Fluid Solutions' Authorized Distributor at <https://www.masterfluids.com/th/en-th/distributors/index.php> or your District Sales Manager, or email us at thailand-info@masterfluids.com.


Physical Properties Typical Data

Color (Concentrate)	Light yellow to amber
Color (Working Solution)	Yellow translucent
Odor (Concentrate)	Mild
Form (Concentrate)	Liquid
pH (Concentrate as Range)	9.5 - 9.9
pH (Typical Operating as Range)	9.2 - 9.8
Coolant Refractometer Factor	1.9

Recommended Metalworking Concentrations

Light Duty	8.0% - 10.0%
Moderate Duty	10.0% - 12.0%
Heavy Duty	12.0% - 15.0%
Design Concentration Range	8.0% - 15.0%

Concentration by % Brix



$\% \text{ Concentration} = \text{Refractive Reading} \times \text{Refractive Factor}$
Coolant Refractometer Factor % Brix = 1.9

Health and Safety

Request SDS



TRIM™ DRIVE G81 NXT

Premium Cutting Fluid for HDD Manufacturing



Mixing Instructions

- Recommended usage concentration in water: 8.0% - 15.0%.
- To help ensure the best possible working solution, add the required amount of concentrate to the required amount of water (never the reverse) and stir until uniformly mixed.
- Use premixed coolant as makeup to improve coolant performance and reduce coolant purchases. The makeup you select should balance the water evaporation rate with the coolant carryout rate. Use our Coolant Makeup Calculator to find the best ratio for your machine: apps.masterfluids.com/makeup/.
- Use mineral-free water to improve sump life and corrosion inhibition while reducing carryoff and concentrate usage.

Ordering Information

20-liter pail

204-liter drum

TRIM™ DRIVE G81 NXT | ©2022-2024 Master Fluid Solutions™ | 2024-11-21

Additional Information

- Use Master STAGES™ Whamex™ for a quick and thorough precleaning of your machine tool and coolant system.
- Consult Master Fluid Solutions before using on any metals or applications not specifically recommended.
- This product should not be mixed with other metalworking fluids or metalworking fluid additives, except as recommended by Master Fluid Solutions, as this may reduce overall performance, result in adverse health effects, or damage the machine tool and parts. If contamination occurs, please contact Master Fluid Solutions for recommended action.
- TRIM™ is a trademark of Master Chemical Corporation d/b/a Master Fluid Solutions.
- Master STAGES™ and Whamex™ are trademarks of Master Chemical Corporation d/b/a Master Fluid Solutions.
- The information herein is given in good faith and believed current as of the date of publication and should apply to the current formula version. Because conditions of use are beyond our control, no guarantee, representation, or warranty expressed or implied is made. Consult Master Fluid Solutions for further information. For the most recent version of this document, please go to this URL:

https://2trim.us/di/?i=th_en-th_DRIVEG81NXT



333/8 Moo 9, Bangpla, Bangplee
Samutprakarn, 10540
Thailand
+662 136 6319

thailand-info@masterfluids.com

masterfluids.com/th/en-th/

